


EPIC® SOLAR 4 GEN2 Kontakte

EPIC® SOLAR 4 GEN2

We stay connected. This is definitely the case with our pin and socket contacts for the EPIC® SOLAR 4 GEN2 solar connectors. The crimp contact provides maximum contact reliability between the contact and the cable, and establishes a vibration-resistant connection. Suitable for conductor cross-sections of 4.0 – 6.0 mm² and automated assembly.

Info

For photovoltaic plants up to 1.5kV system voltage



Benefits

Crimp contact ensures maximum contact reliability between the contact and the cable and establishes a vibration-resistant connection.

Suitable for conductor cross-sections from 4.0 to 6.0 mm².

Large packing unit with 2500 contacts on a roll makes fully automated connector configuration possible.

Application range

For use with EPIC® SOLAR 4 GEN2 solar connectors.

Technical Data

Material: Brass tin-plated

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.



EPIC® SOLAR 4 GEN2 Kontakte

Article number	Packaging unit
44428273	1
44428272	1

Last Update (21.03.2025)

©2025 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16

EPIC® SOLAR 4 GEN2 Kontakte

